



LABELWORKS PX LW-PX800

Installation Manual



Read this document carefully to use this product safely and correctly. If your product is faulty, please read the included warranty card and contact the store you purchased it from. If you require further assistance, contact your local K-Sun customer support center. Please also visit us at www.ksun.com for help and support.

International ENERGY STAR® Compliance Statement


The purpose of the International ENERGY STAR® Program is to promote the development and popularization of energy-efficient office equipment.

As an ENERGY STAR® Partner, Seiko Epson Corporation has determined that this product meets the ENERGY STAR® guidelines for energy efficiency.



Checking Package Contents

Before using the printer, check that you have all the items below. Contact your place of purchase if anything is missing or damaged.



- 1 **LW-PX800**
- 2 **Tape cartridge**
- 3 **USB cable**
- 4 **AC adapter (AST1527Z1-1)**
- 5 **Documents**
Installation Manual (this sheet)
Describes the setup procedures needed to use the printer, and provides information on printer problems and safety. You can download LW-PX800 manuals (PDF) from www.ksun.com.
- 6 **Label Editor Professional CD-ROM (for Windows only)**
Contains the following items:
Software
• Label Editor Professional
Software used for label editing. Use it to create labels to print with the printer.
• Network Configuration Tool
Used to check or change the printer's network settings on the computer connected to the printer.
• Printer driver
To be installed in the computer connected to the printer.

- Instruction manuals**
- Label Editor Professional User's Guide
Describes how to use the Label Editor Professional software.
 - Network Configuration Guide
Provides information not described in this manual on network connection procedures, settings and connection troubleshooting.

To view the documents, you need Adobe Reader.

Opening the instruction manuals

Follow the steps below to view the instruction manuals on the CD-ROM.

1. **Insert the CD-ROM in the computer's CD-ROM drive.**

2. **Click "User's Guide" in the following window.**




3. **Click the manual you want to read in the following window.**



The selected instruction manual is displayed.

Names and Functions of Parts


Front



1. **Power button** Turns the printer power ON/Stand-by
2. **Tape feed button** Perform the tape feed operation.
3. **Wireless button** Each time you press this button, the wireless connection mode switches between Infrastructure Mode, Access point Mode and wireless connection disabled mode. The current mode is indicated by the lamps.
4. **Top cover** Can be opened to insert a tape cartridge, or for print head cleaning.

5. **Open button** Press to open the top cover.
6. **Tape insertion slot for PeelGuard®** PeelGuard® is Tape Corner Trimmer. Insert tape here to round label corners.
7. **Tape outlet** Printed labels come out here.
8. **Error lamp** Flashes when an error occurs.
9. **Wireless LAN connection status lamp** Indicates the wireless LAN connection status.
10. **Direct connection status lamp** Indicates the wireless LAN connection status.
11. **Power status lamp** Indicates the printer's power status.

Rear



1. **USB port** Connects the included USB cable.
2. **LAN port** Connects a LAN cable. *
3. **Security hole** Lets you secure the printer to a desk or post with a commercial security wire lock or similar tool.
4. **Power cord jack** Connects the included AC adapter.
5. **Connect button** Press when setting a wireless LAN connection.

* Use a twisted-pair, Category 5 or higher, straight-through Ethernet cable wired for 10BASE-T or 100BASE-TX.

Meanings of lamps

The lamps indicate printer statuses.

	Stays on while the printer is powered on and in standby status. Flashes during printer operations such as printing.
	Flashes to indicate an error. Check the message displayed on the computer screen.
	Stays on while the printer is connected to a wireless network in Infrastructure Mode, or while the printer is initializing. Flashes while setting up wireless network connection in Infrastructure Mode or while the printer is in the startup process.
	Stays on while the printer is wirelessly connected to a computer or device in Access point Mode, or while the printer is initializing. Flashes while setting up wireless connection in Access point Mode or while the printer is in the startup process.

Symbol Description

	On/Stand-by		Hot surface
	Direct current		Polarity of D.C. power connector

Safety Instructions

For your safety, read the attached documents carefully to use this product correctly. After you have read all instructions, keep this manual handy for future reference and to make your concerns clear. Items below indicate safety precautions to protect users, their surroundings and their property from possible injury or damage. Precautionary notations are categorized as follows according to personal injury and damage to the equipment if the instructions are ignored or the equipment is misused.

WARNING
This symbol indicates information that, if ignored, could possibly result in serious personal injury or even death due to incorrect handling.

CAUTION
This symbol indicates information that, if ignored, could possibly result in personal injury, physical damage, or damage to equipment due to incorrect handling.

The following describes the meaning of each symbol used in the precautions.

	This indicates an important reminder.		This indicates a prohibited item.		This indicates a mandatory procedure.
--	---------------------------------------	--	-----------------------------------	--	---------------------------------------

WARNING

When using the AC adapter and power cable

Do not use any AC adapter or power cable other than the dedicated AC adapter and power cable. Do not use the AC adapter with other than the specified voltage also. Otherwise, damage, overheating, fire or electric shock may occur.

- Take the following precautions when handling the AC adapter and power cable.
 - Make sure to avoid using multiple-socket adapters.
 - Make sure the plug is not dusty before inserting it into an outlet.
 - Insert the plug firmly into the outlet.
 - Do not hold the AC adapter or the plug with wet hands.
 - Do not pull the power cable when disconnecting the plug. Be sure to hold the plug when disconnecting it.
 - Do not make any modification to the AC adapter or power cable.
 - Do not apply strong shocks to or put a heavy object on the AC adapter or power cable.
 - Do not bend or twist the AC adapter or power cable forcibly.
 - Do not place the AC adapter or power cable near a heater.

- Do not use any damaged AC adapter or power cable. Otherwise, damage, overheating or smoking may occur, which may result in fire or electric shock.
- Do not touch the plug during thunderstorms.

When using this product

Do not apply any strong force or shocks to the product such as standing on, dropping or hitting it. Otherwise, the product may be broken, which may result in fire or electric shock. If it is damaged, turn off the power immediately, unplug the AC adapter, and then contact the K-Sun customer support center. Continuous use may result in fire or electric shock.

Take care not to spill any beverage such as tea, coffee or juice onto the product, or to spray aerosol insecticide. It may cause malfunction, fire, or electric shock. If any liquid has been spilled on the product, turn off the power, unplug the AC adapter, and then contact the K-Sun customer support center. Continuous use may result in fire or electric shock.

Do not touch the printhead because it becomes very hot. Otherwise, there is a risk of burns.

Do not open any covers other than the top cover. Doing so may result in fire or electric shock. Always use the product as instructed in this manual. Otherwise, damage or injury may occur.

Never modify or disassemble this product. Doing so may cause fire or electric shock. Do not carry out any operations not described in this manual, or the product may break or cause injury.

If any of the following abnormalities is observed, turn off the power immediately, unplug the AC adapter, and then contact the K-Sun customer support center.

- If smoke, strange odors or unexpected noises come from the product
- If liquid or foreign objects get inside the product
- If the product has been dropped or damaged

Do not touch the tape eject slot, during printing or when the auto cutter is in operation. Otherwise there is a risk of injury.

May exert electromagnetic interference on, and cause malfunction of, cardiac pacemakers. Before using this product, check that there is no one in the vicinity using a cardiac pacemaker.

May exert electromagnetic interference on, and cause malfunction of, sensitive medical equipment. Before using this product, check that there is no sensitive medical equipment in the vicinity.

Use of this product on aircraft may be restricted in some countries. Before using this product, check that use of this product is not restricted on the aircraft.

When handling the auto trimmer

When removing the trimmer box, make sure to turn the power off. If the product operates without the trimmer box, injury or damage may occur with the blade inside the product.

When cleaning the trimmer box, do not touch the trimmer blade, as there is a risk of injury. Do not insert anything other than labels into the trimmer inlet slot. Otherwise, damage to the trimmer may occur.

When handling the auto cutter

Do not touch the tape outlet slot (where the labels come out) during printing or when the auto cutter is in operation. Otherwise, there is a risk of injury.

When handling the half cutter

Do not touch the tape outlet slot (where the labels come out) during printing or when the auto cutter is in operation. Otherwise, there is a risk of injury.

Others

- Do not use or store the product, AC adapter, power cable, USB cable or tape cartridges in the following places.
 - In direct sunlight.
 - Where it may become extremely hot such as in a vehicle with the windows closed.
 - Where it may become extremely hot such as near a heater or the temperature becomes very unstable such as near the exhaust duct of an air conditioner.
 - Where the product may get wet due to a shower or rain such as in a bathroom or outdoors.
 - In a dusty place or where the product may be exposed to smoke or steam such as near the kitchen or a humidifier.
 - On an unstable place such as on a shaly table or on an inclined place.
 - Where it might be subjected to vibration or shock.
 - Near high-voltage power lines or something that generates a magnetic field.

Keep the plastic bags used to contain the product or this manual out of reach of children. Children may suffocate if they swallow them or put their heads into the bags.

CAUTION

When using the AC adapter and power cable

- Do not unplug the AC adapter while the product is in operation, otherwise printing may not be successful.
- Do not use the AC adapter in a small, confined space, or cover it with a cloth. Otherwise, the AC adapter may overheat and deteriorate.

When using this product

Do not stand or put anything heavy on the product or place it on an unstable place such as on a shaly table or on an incline. Otherwise, the product may fall and cause injury.

To ensure safety, unplug this product before leaving it unused.

Before cleaning, make sure to unplug the AC adapter from the outlet.

Do not use a moistened cloth or solvents such as alcohol, thinner or benzene.

Do not block or insert objects into the supplied AC adapter socket or the tape eject slot.

To comply with RF exposure compliance requirements, a distance of at least 22 cm must be maintained at all times between the antenna of this product and people in the vicinity.

Others

The supplied disc is a data CD-ROM for computers. Do not play it in an audio CD player. Otherwise a very loud sound may be emitted, causing risk to both your hearing and your audio equipment.

Be careful of continuous use of which may cause eye fatigue.

When handling tape cartridges

- Make sure to use a dedicated Px Tape.
- Some types of tape cannot be cut by the cutter. For the details, refer to the tape's manual.
- Do not drop it or disassemble it. Doing so may cause damage.
- Do not pull out the tape forcibly by hand. But make sure to feed the tape. Otherwise, the tape cartridge may be broken and unusable.
- Avoid using a tape cartridge without remaining tape. Doing so may cause overheating of the printhead, which may result in damage or malfunction.

MEMO

Tape cartridges contain ink ribbons in them. When disposing of tape cartridges, make sure to follow the local regulations for disposal.

CD-ROM software

Take care to prevent the CD-ROM from being subjected to excessive force or becoming scratched. Do not store the CD-ROM in excessively hot or cold locations.


Cleaning

WARNING
To prevent the risk of cuts, never insert fingers in the PeelGuard®.

CAUTION
Always turn the printer OFF before cleaning. Always use dedicated tape cartridges having the symbol.

PeelGuard®

1. Pull out the tray.
2. Remove the tape scraps, then insert the tray back in the printer.



Printer


Wipe the printer with a soft, dry cloth. Never use solvents or chemicals such as benzene, paint thinner or alcohol. Never use a chemical cloth.

Print head

If streaks or smears appear on printouts, use a cotton swab or similar materials to wipe dirt off the print head.

1. Press the button to open the top cover.


2. Clean the print head.
3. Close the top cover.



MEMO
Instead of the cleaning method described here, you can use an optional cleaning cartridge to clean the print head. For more information, contact the K-Sun customer support center.

Replacing the tape cartridge

1. Press the button to open the top cover.
2. Remove the tape cartridge by pressing on the tabs on both sides.
3. Place a new tape cartridge in the printer.
4. Close the top cover.



Specifications

Printer

Dimensions	Approx. 123 (W) x 153 (D) x 139 (H) (mm)
Weight	Approx. 1,080 g
Supported tape width	4 mm, 6 mm, 9 mm, 12 mm, 18 mm, 24 mm, 36 mm
Interface	USB 2.0 Full-speed, wired LAN (10/100BASE-TX), wireless LAN (IEEE 802.11b/g/n)
Power supply	
Type	AST1527Z1-1
Manufacturer	Seiko Epson Corp.
Input	AC100-240V, 0.9A, 50-60Hz (dedicated adapter, power cable only)
Output	DC15V, 2.7A
Total output power	41 W
Operating temperature	5 to 35 degrees C
Storage temperature	-10 to 55 degrees C

Operating environment

Operating system	Windows, Mac OS X, iOS, Android
Hard disk space which Label Editor Professional uses	Windows: Approx. 300MB, Mac OS X: Approx. 40MB
Drive	CD-ROM drive
Display	XGA (1024 x 768), High Colour or higher
Interface	USB 2.0 Full-speed, wired LAN (10/100BASE-TX), wireless LAN (IEEE 802.11b/g/n)

See other side for how to use printer.

Using the Printer

This section describes all the procedures from printer setup to printing and attaching a label. The descriptions of computer connection and other procedures are for Windows. If using the Mac OS X operating system, refer to the "Label Editor Lite for Macintosh User's Guide."


CAUTION
Do not connect connection cables to the printer until you are instructed to do so.

Printer Setup

1. Connecting the power cable

CAUTION
Always use the AC adapter provided.

1. Connect the AC adapter provided (AST1527Z1-1) to the printer, and plug the power plug into a power outlet.




Auto power-off
The printer's power turns off automatically when the printer has not been used for about 8 hours.

2. Inserting the tape cartridge in the printer

CAUTION
Always perform the tape feed operation after inserting a tape cartridge in the printer.

1. Remove any slack in the tape inside the tape cartridge.




2. Press the button to open the top cover.



3. Place a tape cartridge in the printer as shown.

Pass the end of the tape through the gap.



4. Close the top cover.




5. Perform the tape feed operation.

- 1) Press the button to turn the printer power ON.
- 2) Press the button.

Determining the computer connection method

The printer supports wireless LAN connection, wired LAN connection and USB cable connection. The connection method will vary according to the environment it is installed in. Use the flowchart below to carry out the connection procedure.

MEMO
Wireless LAN connection, wired LAN connection and USB connection can be used at the same time in any combination.




USB Cable Connection to Computer

Install the printer driver after installing the Label Editor Professional software.

1. Installing the "Label Editor Professional" software in the computer

1. Insert the CD-ROM provided in the CD-ROM drive of the computer to be connected.



1. Select the language to use.

2. Click



1. Click

4. The "License Agreement" screen appears. Read the information, then click "Agree".



6. Perform the operations described in the on-screen instructions. When the installation completion message appears, click "Finish". Application software installation is now completed.

Next, install the printer driver. Go to Procedure 2.

2. Installing the printer driver



1. Select


2. Click



1. Select

2. Click

3. 1. Turn the printer power ON.
2. Connect the computer and printer with the USB cable.



4. When the installation completion screen appears, click "Finish".

The setup procedure is now completed. Start the Label Editor Professional software to create a label.

Wireless LAN Connection to Computer

Install the software after making the printer and access point network settings.

1. Specifying the network connection method

MEMO
The procedure given here applies when making the printer's network settings for the first time. If you have already made the network settings, see the Network Configuration Guide.

1. Insert the CD-ROM provided in the CD-ROM drive of the computer to be connected.



3. Please select one of the following options.



2. Printer and access point operations


1. Turn the printer power ON as directed in the on-screen instructions.
2. Press the button until the lamp flashes.




2. Press the printer's Connect button as directed in the on-screen instructions.



3. Press the WPS button for the access point as directed in the on-screen instructions.



The settings have been made when the printer's lamp stops flashing and lights steadily. The settings information is saved in the printer.



Next, install the software in the computer. Go to Procedure 3.



Next, make the printer and access point settings. Go to Procedure 2.

3. Software installation



3. When the installation completion screen appears, click "Finish".

The setup procedure is now completed. Start the Label Editor Professional software to create a label.

Creating a Label

1. Creating a label


Use the label editing software "Label Editor Professional" to create labels. See the Label Editor Professional User's Guide for the detailed procedures. Label Editor Professional User's Guide

2. Printing a label

Printing operations are done from the computer connected to the printer. See the Label Editor Professional User's Guide for the detailed procedures. Label Editor Professional User's Guide

3. Attaching a label

1. Peel off the backing paper.
2. Attach the label and rub it firmly.




MEMO
If you set the tape cutting method to "Half cut", only the label surface is cut when several labels are printed consecutively, making it easier to peel off the labels. See the Label Editor Professional User's Guide for the detailed procedures. Label Editor Professional User's Guide

Rounding label corners with PeelGuard®

You can round label corners with PeelGuard® Tape Corner Trimmer.

1. Insert the tape in the tape insertion slot, following the guide.



Troubleshooting

This section describes how to resolve printer operation and label printing problems. See the Network Configuration Guide for how to deal with network settings or connection problems.

Printer's button does not light.

Check that the power cable is properly connected. If the button still does not light, contact your place of purchase or the K-Sun customer support center.

Printer does not print when print operation is directed.

- If a message is displayed on your computer screen, check the message information.
- Check that connection cables are connected properly, that the tape cartridge is mounted properly, and that the cover is closed properly.
- Have you selected the printer to be used? Printing will not be done properly if another printer is selected.
- Did you restart the computer after installing the printer driver? The printer driver may not be installed correctly if the computer was not restarted. Reinstall the printer driver.

Text is not printed properly.

- Check that the tape cartridge is properly mounted.
- Print at a low speed. Change the setting in the printer settings of the printer driver.

Lines appear on printed labels.

The print head is dirty. Clean the print head.

Canceling a print job

Check the printer's power is ON, then press the button on the front of the printer briefly once.

Labels are not cut automatically

- Check if the cut setting is set to "Don't cut" in the printer settings of the Label Editor Professional software. Label Editor Professional User's Guide
- Is the cutter blade worn? Prolonged use of the cutter can wear down and blunt the blade. Contact the K-Sun customer support center.

Half cut function doesn't work properly.

- Is the printer set to "Half cut" or "Don't cut"? Check the settings.
- Is the cutter blade worn? Prolonged use of the cutter can wear down and blunt the blade. Contact the K-Sun customer support center.

Trimmer doesn't cut properly.

- Is the printer printing? The trimmer doesn't operate during printing.
- Was the label inserted properly in the trimmer tape insertion slot? Insert the label into the slot following the guide.
- Is the printer clogged with tape scraps? Remove the trimmer cover, and remove the tape scraps.
- Are you using a tape whose width is 6 mm or shorter? You cannot cut those narrow tapes with the trimmer.
- Is the cutter blade worn? Prolonged use of the cutter can wear down and blunt the blade. Contact the K-Sun customer support center.