



The Labels You Want When You Need Them.®

Material 169: Gloss White Paper Label
with Removable Adhesive for Kiaro! Inkjet Label Printing

Facestock:

Description: White paper label with gloss finish is uniquely receptive to Kiaro! inkjet label printing provides durability, ideal for printing photographic images on primary display labels which must resist moisture and some solvents.

Thickness: 4 Mil (104 Microns)

Gloss: 80%

Brightness: 93%

Adhesive:

Description: This is a removable, solvent-free adhesive that meets European regulations pertaining to direct and indirect contact with food (EC Directive 85/572/EEC).

- Type: Acrylic dispersion
- Thickness: 0.8 Mils (20 Microns)
- Initial Tack: 1.5 – 4.0 N (to glass)
- Tackiness: 1.5 – 4.0 N/25mm (after 20 minutes, to glass)
- Shear Adhesion: >1 hour (to steel)

Liner:

Description: White paper release liner with polydimethylsiloxan coating.

Caliper: 2 Mil (55 Microns)

Tensile:

MD: 5.0 kN/m

CD: 2.3 kN/m

Tear:

MD: 240 mN

CD: 260 mN

Total Construction Caliper: 6.8 Mil (173 Microns)

Minimum Application Temperature: 14° F (-10° C)

Service Temperature Range: -4° F to +176° F (-20° C to 80° C)

Storage Considerations:

QuickLabel warrants that this label/tag product retains its performance properties for two years from the date of purchase if properly stored at room conditions between 68-84°F (18-29°C) and 30-70% relative humidity. Do not store in direct sunlight. Do not remove protective packaging until product is to be used.

Recommended Applications: Material# 169 is ideal for printing glossy paper labels using the Kiaro! inkjet label printer, especially in applications that require temporary or long-term label removability.

Updated on: 12/29/15