



Material 190: Clear Gloss Polypropylene Label for Kiaro! Inkjet Label Printing

Facestock:

Description: Transparent, glossy polyethylene label uniquely receptive to Kiaro! inkjet label printing provides durability, ideal for printing photographic images on primary display labels that must resist moisture and solvent exposure.

Thickness:

3.1 Mil (79 Microns)

Adhesive:

Description: This clear, permanent acrylic dispersion adhesive is UV-stable and has good heat resistance.

- Type: Permanent acrylic adhesive
- Thickness: 0.8 Mils (20 Microns)

Liner:

Description: White kraft paper release liner.

Caliper: 2.6 Mil (66 Microns)

Total Construction Caliper: 6.5 Mil (165 Microns)

Minimum Application Temperature: 23° F (-5° C)

Service Temperature Range: -20° F to +212° F (-29° C to 100° C)

Storage Considerations:

QuickLabel warrants that this label/tag product retains its performance properties for one year from the date of purchase if properly stored at room conditions between 64-84°F (18-29°C) and 30-70% relative humidity. Do not store in direct sunlight. Do not remove protective packaging until product is to be used.

Recommended Applications: Material# 190 is ideal for printing transparent labels using the Kiaro! inkjet label printer, especially in primary display label printing applications that demand water-resistance and UV-light resistance, such as cosmetics and retail labeling.

Updated on: 12/29/15