



The Labels You Want When You Need Them.®

Material 198: White Polypropylene Label with Satin Finish for Kiaro! Inkjet Label Printing

Facestock:

Description: White polypropylene label with satin finish uniquely receptive to Kiaro! inkjet label printing provides durability, ideal for printing photographic images on primary display labels which must resist moisture and solvent exposure.

Thickness:

3.5 Mil (89 Microns)

CIE Whiteness: 104%

Opacity: 86%

Adhesive:

Description: This general-permanent adhesive performs well at low temperatures and adheres well to a wide variety of substrates, including cardboard.

- Type: Emulsion adhesive

Liner:

Description: White kraft liner.

- Caliper: 2.4 Mils $\pm 10\%$ (61 Microns)

Total Construction Caliper: 6.4 Mils (163 Microns)

Minimum Application Temperature: 32° F (0° C)

Service Temperature Range: -4° F to +176° F (-20° C to 80° C)

Storage Considerations:

QuickLabel warrants that this label/tag product retains its performance properties for one year from the date of purchase if properly stored at room conditions between 64-84°F (18-29°C) and 30-70% relative humidity. Do not store in direct sunlight. Do not remove protective packaging until product is to be used.

Recommended Applications: Material# 198 is ideal for use in inkjet label printing applications in which durability and long-term adhesion to surfaces is required. This material is not recommended for labeling highly curved surfaces.

Updated on: 12/29/15