

Material 206: Gloss White Polypropylene Label on Clear PET Liner, for use in Kiaro! printers with external unwinder

Facestock:

Description: A gloss white polypropylene label uniquely receptive to Kiaro! inkjet label printing. Durable and ideal for photographic images used in primary displays where moisture and/or solvent resistance is required.

Caliber:Basis Weight:3.5 mil49 lbs/ream

Opacity: CIE Whiteness:

84% 90%

Adhesive:

Description: Clear permanent adhesive designed for applications requiring excellent wet-out properties, clarity and UV stability. Good adhesion properties and heat resistance.

• **Type**: Emulsion Acrylic

Liner:

Description: Clear PET

Basis Weight: 23 lbs/ream ±10% Caliper: 1.2 mil (30.5 microns)

Total Construction Caliper: 5.4 mil ±10%

Minimum Application Temperature: 23°F (-5°C)

Service Temperature Range: -20°F to + 212°F (-28°C to 100°C)

Storage Considerations:

QuickLabel warrants that this label/tag product retains its performance properties for one year from the date of purchase if properly stored at room conditions between 64-84°F (18-29°C) and 30-70% relative humidity. Do not store in direct sunlight. Do not remove protective packaging until product is to be used.

Recommended Applications:

Material #206 is ideal for use in Kiaro! where an external unwinder is used. Recommended in automatic labelers where liner strength is required.

Updated on: 06/30/2016