

Material 208: Gloss White PET Label for use in Kiaro! & QL-111 Printers. Specially engineered for great adherence to rough surfaces such as tires, cardboard, wood, jute and the likes.

Facestock:

Description: A gloss white PET label especially engineered for use in dye-based Inkjet Printers. It couples brilliant inkjet print quality with fast ink drying time, high temperature and moisture resistance.

Thickness: 3.1 Mil $\pm 10\%$ (79 Microns)

Adhesive:

Description: Rubber-based, transparent hot melt ideally suited for adhesion to tires, wood, jute and any other rough or porous surfaces.

• **Type**: Hot Melt Rubber, 40g/sqm

Liner:

Description: Double-sided siliconized glassine liner

Caliper: 2.16 Mils ±10% (55 Microns)

Total Construction Caliper: 6.9 Mils ±10% (174 Microns)

Minimum Application Temperature: 23°F (-5°C)

Service Temperature Range: -40° F to +122° F (-5° C to 50° C)

Storage Considerations:

QuickLabel warrants that this label/tag product retains its performance properties for one year from the date of purchase if properly stored at room conditions between 64-84°F (18-29°C) and 30-70% relative humidity. Do not store in direct sunlight. Do not remove protective packaging until product is to be used.

Recommended Applications:

Material #208 is ideal for use in Kiaro! & QL-111. It features excellent water resistance and superior adhesion to rough surfaces.

Updated on: 10/20/2016